ZR432-2PAV

ZR432-2PAV RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE & RED VISUAL INDICATOR



ZR432-2PAV

ZR432-2PAV RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE & RED VISUAL INDICATOR

Specyfikacja techniczna

General

Wireless frequency	868 MHz
Addressing method	Electronic, Unique address embedded

Electrical

Power supply type	Batterier

Detection

Monitoring	Continuously self-checking
Alarm temperature (maximum)	+70°C
Alarm temperature (minimum)	+54°C

Physical

Colour	Polær hvid
Mounting type	Samling på underlag, Overflademontering
Material (body)	Støbt ABS

Environmental

Vandal proof	No
Application temperature (maximum)	+50°C
Application temperature (typical)	+25°C
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Wyroby zgodne

Kategoria	Odniesienie	Opis
Detection device	11510-ZT	ZPL1-1 ADD.LABEL 1001-1127
Detection device	11520	Zpl1-2 Add.Label 2001-2127
Detection device	11530-ZT	ZPL1-3 ADD.LABEL 3001-3127
Detection device	11540-ZT	ZPL1-4 ADD.LABEL 4001-4127

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57