ACT736-37


Duo proximity card sitecode 37

Overview

The DuoProx card offers a solution for companies desiring to use one card, requiring dual technologies, for multiple applications.

Features

By combining two technologies on one card, the DuoProx card provides the benefits of proximity for access control applications, and meets the requirements for industry standard magnetic stripe applications.



Details

- Offers universal compatibility with all HID proximity readers
- Provides an external number for easy identification and control
- HID standard 32-bit configuration
- Meets ISO standards for thickness; Use with all direct image or thermal transfer printers
- Accepts either a horizontal or vertical slot punch

ACT736-37

Duo proximity card sitecode 37

Technical specifications

System

Reading distance	MiniProx reader: 5 to 10 cm ThinLine II reader: 5 to 10 cm ProxPro reader: 10 to 15 cm MaxiProx reader: 25 to 40 cm
Supported readers	HID Proximity Readers, Magstripe Readers

Technology

Credential type	Magstripe, Proximity
Credential operating frequency	125 KHz

Physical

Form factor	CR80 (Credit)
Physical dimensions	54 x 87 x 0.8 mm (W x H x D)
Net weight	6.8 g

Environmental

Operating temperature	-45 to +70°C
Relative humidity	5 to 95% noncondensing

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 29 April 2024 - 14:03