# FCX-176-001

## Fusion Wireless Heat Detector Class CS

### General

The FCX-176-001 heat detector is an addressable detector to be used with a wireless base. It uses a fixed temperature alarm threshold at 90°C.

The FCX-176-001 is quick and easy to install by simply fitting to a compatible wireless base.

### The Range

The Fusion series consists of:

· Optical Smoke Detectors
· Multisensor Smoke Detectors
· A1R Heat Detectors
· CS Heat Detectors
· Sounders in red and white
· Combination Sounder VIDs and VADs
· Manual Call Points
· Interface Modules

### Operating Principle

Wireless devices are often installed in buildings where wiring presents a challenge because the fabric of the building or its design is negatively affected by the use of cables. It could also be difficult to introduce cable runs into heritage buildings. It is for these architecturally sensitive buildings that the Fusion series was developed.

Every Fusion device is assigned an address from is base. This address is converted by the Fusion wireless loop interface to a device address similar to a wired device connected directly to the loop wiring.



### Details

- Fire indication LED
- Anti tamper locking mechanism
- FasTest maintenance feature
- Third party EN certified
- Easy to install
- Proven technology
- Self-monitoring

# FCX-176-001

## Fusion Wireless Heat Detector Class CS

## Technical specifications

### General

| | |
|---|---|
| Status indication | LED |
| User interface | LED |
| Compatibility | Wireless base FCX-170-001, FCX-191-000, FCX-191-100 or FCX-191-200 |
| Alarm levels | EN54-5 Class CS |

### Electrical

| | |
|---|---|
| Power supply type | Batteries |
| Operating voltage | 2.8 to 5 VDC |

### Detection

| | |
|---|---|
| Detection principle | Heat |
| Monitoring | Device type, Presence |
| Sensitivity | Fixed |
| Alarm temperature (maximum) | +100°C |
| Alarm temperature (typical) | +80°C |
| Alarm temperature (minimum) | +84°C |
| Rate-of-rise | Not supported |

### Physical

| | |
|---|---|
| Physical dimensions | 113 x 81 mm (Ø x H) - Including base |
| Net weight | 400 g - Including base |
| Colour | White |
| Mounting type | Base mount |
| Material (body) | Polycarbonate |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Operating temperature | -10°C to 55°C |
| Storage temperature | 5°C to 30°C |
| Application temperature (maximum) | +80°C |
| Application temperature (typical) | +55°C |
| Relative humidity | < 95% noncondensing |
| Environment | Indoor |
| IP rating | IP23 |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 2, WEEE |
| Certification | BOSEC, CPR |
| Standards | EN54-5<br>EN54-13 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 2 June 2026 - 12:04