C-9403

Conventional Sounder, Multi Tone, Shallow Base w/ Visual Indicator

General

The C-9403 is conventional sounder with VID is an audible fire alarm device with a high intensity LED visual indicator bank. It gives an audible and visual alarm signal when 24 VDC is applied to its inputs.



Details

- High sound output
- 2 User selectable tones
- Shallow mounting base with optional deep base
- Two part construction with base mounted termination for easy installation
- LPCB marked

C-9403

Conventional Sounder, Multi Tone, Shallow Base w/ Visual Indicator

Technical specifications

General

Compatibility	GST conventional systems

Electrical

Power supply type	24 VDC
Operating voltage	20 to 28 VDC (24 VDC typical)
Current consumption	≤ 35 mA
Cable size	> 1.5 mm²

Sounder

Output level	≥ 95 dB @ 1 m Continuous
Frequency	Selectable
Selectable tones	2

VID

Colour	Red
Flash frequency	2 Hz (±20%)

Physical

Physical dimensions	110 x 95.9 mm (Ø x H)
Shipping weight	327.2 g
Colour	Red
Mounting type	Base mount
Mounting position	Ceiling, Wall
Mounting base	Shallow
Material	ABS

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	< 95% non-condensing
Environment	Indoor
IP rating	IP33C

Regulatory

Compliancy	CE, REACH, RoHS, WEEE
Certification	CPR
Standards	EN54-3

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 10:33