C-9404

Conventional Sounder, Multi Tone, Shallow Base

General

The C-9404 conventional sounder is an audible fire alarm device. It gives an audible alarm signal when 24 VDC is applied to its inputs.



Details

- High sound output
- 2 Tones user selectable
- Shallow mounting base with optional deep base
- Wiring directly to base for easy installation
- LPCB Marked

C-9404

Conventional Sounder, Multi Tone, Shallow Base

Technical specifications

General

Compatibility	GST conventional systems

Electrical

Power supply type	24 VDC
Operating voltage	20 to 28 VDC (24 VDC typical)
Current consumption	≤ 35 mA
Cable size	> 1.5 mm²

Sounder

Output level	≥ 95 dB @ 1 m Continuous
Frequency	Selectable
Selectable tones	2

Physical

Physical dimensions	110 x 95.9 mm (Ø x H)
Shipping weight	327.2 g
Colour	Red
Mounting type	Base mount
Mounting position	Ceiling, Wall
Mounting base	Shallow
Material	ABS

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	95% non-condensing
Environment	Indoor
IP rating	IP33C

Regulatory

Compliancy	CE, REACH, RoHS, WEEE
Certification	CPR
Standards	EN54-3

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 10:33