# FE130MS

**Serratura magnetica Eco Line 300 Kgf montaggio standard.**

## Description

Eco Line magnetic lock 300 kgs, monitored. Surface mounting.

## Application

Medium security applications for internal and external doors. To be mounted inside external doors.

## Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

## Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



## Dettagli

- 300 kgf holding power
- Surface mounted
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Monitored changeover

# FE130MS

## Serratura magnetica Eco Line 300 Kgf montaggio standard.

## Specifiche tecniche

### General

| | |
|---|---|
| Product type | Magnetic lock |

### Monitoring & status

| | |
|---|---|
| Monitored | Yes |
| LED indicator | Yes |
| Door status switch | No |
| Monitored changeover | Yes |
| Magnetic bond sensor | Yes |

### Physical

| | |
|---|---|
| Colour | Aluminium |
| Finish | Vapour blasted aluminium |

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57