ZR432-2PA

ZR432-2PA RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE



ZR432-2PA

ZR432-2PA RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE

Technische specificaties

General

Wireless frequency	868 MHz
Addressing method	Electronic, Unique address embedded

Electrical

Power supply type	Batteries

Detection

Monitoring	Continuously self-checking
Alarm temperature (maximum)	+70°C
Alarm temperature (minimum)	+54°C

Physical

Colour	Polar white
Mounting type	Base mount, Surface mount
Material (body)	Moulded ABS

Environmental

Vandal proof	No
Application temperature (maximum)	+50°C
Application temperature (typical)	+25°C
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Compatibele producten

Categorie	Referentie	Beschrijving
Detection device	11510-ZT	ZPL1-1 ADD.LABEL 1001-1127
Detection device	11520	Zpl1-2 Add.Label 2001-2127
Detection device	11530-ZT	ZPL1-3 ADD.LABEL 3001-3127
Detection device	11540-ZT	ZPL1-4 ADD.LABEL 4001-4127

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57