ACA-B706SS-100

LHD Cable Accessory - Bracket "7", 6 0mm (2.4") (St Steel) w/ Sleeve - Pack of 100

Pipe Clip

The ACA-B706 series 7-bracket (pipe clip) is designed to utilise existing pipework running through the protected area as a fixture for the liner heat detection cable. The ACA-B706 is designed to fit any pipe diameter. A silicon protection sleeve is supplied with the unit to protect the linear heat cable when fastened to the bracket.



Installation

The ACA-B706 should be fitted to the underside of the pipe and secured in place using suitable cable ties or strapping. The hole in the end of the bracket allows for the securing of the sensor cable using a silicone sleeve and cable tie. Alternatively an I-bracket (distance piece) may be connected to the 7-bracket to extend the position of the sensor cable. Without an extension the 7-bracket (pipe clip) supports the sensor cable approx. 60mm below the pipe.

Recommended spacing: 1m

Details

- Easy installation of linear heat cable
- For use on existing pipes in the area
- Available in stainless steel
- Available in quantities of 100

ACA-B706SS-100

LHD Cable Accessory - Bracket "7", 6 0mm (2.4") (St Steel) w/ Sleeve - Pack of 100

Technical specifications

Physical

Physical dimensions	20 x 60 x 50 mm (W x H X D)
Net weight	2.3 kg
Mounting type	Zum Anklipsen
Material (body)	Rostfreier Stahl

Environmental

Environment	Drinnen, Draussen

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 4 January 2024 - 15:13