FC-315-WA1

Wireless, white, wall mount SDR VAD Head only

The FireCell Wireless Wall Sounder Beacon is quick and easy to install, offering individual addressing at the fire control panel. This device comprises of a sounder beacon and a wireless sounder base.

Works with FC-171-001 White Wireless Sounder Base



Details

- 0.5 Hz / 1 Hz beacon flash selection
- 32 selectable tones
- Integrated audio monitoring
- Volume control
- Anti tamper locking mechanism
- Third party EN certified

FC-315-WA1

Wireless, white, wall mount SDR VAD Head only

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	FC-171-001

Electrical

Power supply type	Batterien
Batteries	Powered by radio base

Sounder

Output level	< 99 dB(A) @ 1 m (Tone dependant)
Output level adjustment	Analogue
Frequency	Selectable
Selectable tones	32
No. of stages	2

VAD

Colour	White flash
Rating	W-3.1-11.3
Flash frequency	0.5 Hz / 1 Hz (selectable)

Physical

Physical dimensions	120 x 145 mm (Ø x D)
Net weight	0.65 kg
Colour	Weißes Gehäuse / weißer Blitz
Mounting type	Wandmontage
Mounting position	Wand
Mounting base	Drahtlos

Environmental

Vandal proof	Yes
Operating temperature	-10 to 55 °C
Environment	Drinnen

Regulatory

Compliancy	CE
Certification	BOSEC, CPR
Standards	EN54-23 EN54-3 EN54-13

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 2 June 2026 - 12:24