# KE-DM3010G-IP

**Excellence Series intelligent addressable manual call point, weatherproof**

## General

The DM3000 Series is an intelligent range of addressable manual call points. The DM3010G-IP is a weatherproof, green, single action MCP with a Running-Man functional indication. It is delivered complete with resettable element, test connector and test key. Multiple optional accessories are available to facilitate most in- and outdoor installation requirements.

## Aesthetics

This weatherproof single action MCP is a standard profile MCP suitable for surface mount installations. It is supplied with a colour matched weatherproof back box. With its designer dual, tricolour LEDs it offers 180°, clear local indication of its operational status, even from a side view. The clean face of the MCP is further enhanced by a front access & test key facility.

## Installation & maintenance friendly

The front facing access for an aesthetically matching test key allows unhindered access regardless of the installation location. The MCP key doubles as a test and disassembly tool allowing removal of the MCP front cover without the need for additional tools.

## Compatibility

The DM3000 range may be used on compatible Aritech fire systems. They can in many cases be deployed into existing systems without CIE configuration changes.




## Details

- Reliable single action manual call point for surface mounting
- Dual, tri-colour status indicators offers 180° alarm visibility
- Tamper resistant design with resettable or frangible element
- Unobtrusive front facing test facility
- Standard mounting options facilitates easy retrofitting to existing installations
- Back box with rear, top and bottom cable entry
- Screen connection terminal in the back box for electrically noisy installations
- Pluggable connector with link through facility for ease of installation and pre-commissioning testing
- An alarm flag on the face of the manual call point allows alarm indication even without alarm LEDs
- Fast, no-tools-required maintenance using the test key
- Up to 128 devices supported per loop

# KE-DM3010G-IP

## Excellence Series intelligent addressable manual call point, weatherproof

## Technical specifications

### General

| | |
|---|---|
| Status indication | Dual LEDs, Alarm (red constant),<br>Isolated (yellow constant),<br>Fault (yellow blinking),<br>Communication (green blinking) |
| User interface | LEDs, Alarm Flag |
| Compatibility | Excellence and legacy Aritech series fire systems |
| Connectivity | 2-wire loop |
| Addressing method | Dip-Schalter |

### Electrical

| | |
|---|---|
| Power supply type | Loop-Stromversorgung |
| Operating voltage | 17 to 29 VDC |
| Communication voltage | 4 to 11 V pulsed |
| Current consumption | 180 µA (Quiescent)<br>2.8 mA (Alarm) |
| Cable specification | 0.404 to 2.05 mm |
| No. of cable cores | 2 |
| Terminals | 4 (A+/A-;B+/B-) |

### Detection

| | |
|---|---|
| Detection principle | Push button/switch |
| Monitoring | Activated, Fault, Off |
| Response time | < 3 s |
| Installation height | Determined by local regulation |

### Physical

| | |
|---|---|
| Physical dimensions | 87 x 87 x 26 mm (w/o back box)<br>87 x 87 x 57 mm (w/ back box) |
| Net weight | 267 g (w/ back box) |
| Colour | Grün (RAL 6024) |
| Mounting type | Wandmontage |
| Cable entries | 1 × threaded MK20 (Top or bottom), 2 × threaded MK20 (Bottom or top) |
| Material (body) | Schwer entflammbares ABS |
| Functional marking | Running Man |

### Environmental


| | |
|---|---|
| Vandal proof | No |
| Operating temperature | −25 to +72°C |
| Storage temperature | −25 to +72°C |
| Relative humidity | 10 to 95% noncondensing |
| Environment | Drinnen, Draussen |
| IP rating | IP41 |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, UKCA, WEEE |
| Certification | CE |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Detection device | N-MC-FC | MCP accessory, intelligent Manual Call Point flip cover |
| Detection device | N-MC-FE | MCP accessory, intelligent manual call point frangible element |




KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 11 August 2026 - 14:24