# TESTIFIRE-ADAP

## XTR2 Adaptor for aspiration and flat detectors

### General

The TESTIFIRE-ADAP is a  specialist adaptor to replace the standard membrane on a Testifire XTR2 test cup. It enables functional testing of aspirating smoke detection systems. It can also be used to test flat/flush detectors.



### Details

- Fits to Testifire XTR2 in place of standard membrane
- Allows placement around ASD pipe and alignment with sampling hole
- Also suitable for use with flat or flush mounted detectors

# TESTIFIRE-ADAP

## XTR2 Adaptor for aspiration and flat detectors

## Technical specifications

### Physical

| | |
|---|---|
| Colour | Schwarz |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Operating temperature | 5 to 45°C (41 to 113°F) |
| Storage temperature | -10 to 50°C (14 to 122°F) |
| Relative humidity | 0 to 85% non-condensing - operating<br>0 to 90% non-condensing - storage |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, WEEE |

### SKU info

| | |
|---|---|
| Product brand | testifire |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Test Equipment | TESTIFIRE-XTR2 | All-in-one connected smoke/heat detector test kit |
| Test Equipment | TESTIFIRE-XTR2-6M | All-in-one connected smoke/heat detector test kit to 6 m |
| Test Equipment | TESTIFIRE-XTR2-HEAD | All-in-one connected smoke/heat detector test head |

EDWARDS
*Built for Resilience*

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 October 2024 - 13:46