D-92WPB

IP66 weatherproof box for DI-9204, DC-9204, DI-M9204 & DC-M9204 Manual Call Points

General

The D-92WPB Weather Proof Box is designed to provide weatherproofing for manual call points in outdoor applications. In addition to protecting the MCP from accidental activation, it is also an effective guard against physical damage.

Application

Internal space is designed to suit most types of European style MCPs.

Installation

The D-92WPB is designed for surface mounting and may be installed on any solid wall or support.



Details

- IP65 Protection for a standard manual call point
- Allows for a 2 step operation avoiding accidental activation: - open the cover - activate the manual call point
- Clear and durable protective housing
- Surface mounting for easily installation
- Standard (60 mm) hole spacing and sufficient internal space to suit most European style MCPs
- Added space for optional micro-switch, battery, and buzzer if needed

D-92WPB

IP66 weatherproof box for DI-9204, DC-9204, DI-M9204 & DC-M9204 Manual Call Points

Technical specifications

Physical

Physical dimensions	188 x 125 x 86 mm (L x W x H)
Colour	Transparent
Material	ABS

Environmental

Vandal proof	No
Operating temperature	-20 to +55°C
Relative humidity	<95% noncondensing
Environment	Drinnen, Draussen

Regulatory

Compliancy	CE, REACH, RoHS, WEEE

Compatible products

Category	Reference	Description
Detection device	DC-9204E	Innovation Conventional Manual Call Point
Detection device	DI-9204E	Innovation Intelligent DI-9000E Series Addressable Manual Call Point

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 20 February 2025 - 15:35