2010-2A-PAK-HPL

Chiave attivazione High Power Loop per centrale 2X-A

Overview

The fire panel allows for its capabilities to be extended by use of USB dongles. These USB dongles are called PAK, which stands for Panel Activation Key. The use of the PAK will activate additional high-end feature(s) in the panel. Depending on the required functionality, separate and multiple PAKs can be used to enable these functionalities. Functionalities like number of nodes/loops, supported detector protocol, used TCP/IP communication protocol for remote monitoring, communication towards management software like BACNet or Modbus, etc, can be enabled by usage of the PAKs. The PAK is tied to the serial number of the panel, but does not have to stay connected to the panel. It can be removed once the PAK has been installed, and the feature is enabled in the panel. It is therefore recommend that PAKs stays with the panel at all time, for example in case of performing reset functions or re-installations.



Dettagli

- High Power Loop
- Compatible with panel firmware 3.1. or higher
- USB interface type 2.0

2010-2A-PAK-HPL

Chiave attivazione High Power Loop per centrale 2X-A

Specifiche tecniche

Physical

Fattore di forma	Lille
Tipo di montaggio	I kabinettet

Regulatory

Certificazioni	EN54-13, EN54-2

In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 12 November 2026 - 18:57