Z-AUXD-2P

Deep base mounting, polar white

General

The Z-AUXD-2P is a surface mounting base accessory that allows detectors to be installed using standard 20 or 25 mm electrical conduit. Four flat surfaces are provided on the wall of the moulding to accommodate side entry glands, together with a breakout in the base of the unit for rear entry cables.

The Z-AUXD-2P is compatible with all ZP7 and Z6 series detector bases. It features fixing slots for either direct ceiling mounting, or alternate connection to most standard conduit boxes.



Details

- Accepts conduit sizes up to 25 mm
- Compatible with all ZP7 and Z6 series detector bases
- Side and rear wiring entry

Z-AUXD-2P

Deep base mounting, polar white

Technical specifications

General

Compatibility	ZP7/Z6 series addressable and conventional bases

Physical

Physical dimensions	115 x 45 mm (Ø x D) 25 mm (max. conduit diameter)
Net weight	165 g
Colour	Blanc polaire
Mounting type	Loftmontering, Conduit box, Montage en surface
Material (body)	Støbt ABS

Environmental

Operating temperature	-10 to +55ºC
Relative humidity	20 to 95% noncondensing
Environment	Indendør

Compatible products

Category	Reference	Description
Detection device	ZP7-IB2-P	Ziton series point detector base with isolator
Detection device	ZP7-SB1-P	ZP7 Series point detector base
Notification device	ZP7-SBB-P	Ziton series surface mount visual indicator base, PW

KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 14 October 2026 - 17:04