ZR432-2P

ZX432-2P RADIO DUAL OPTICAL/HEAT DETECTOR /W ZR401-3 BASE & BATTERY PACK (POLAR WHITE)



ZR432-2P

ZX432-2P RADIO DUAL OPTICAL/HEAT DETECTOR /W ZR401-3 BASE & BATTERY PACK (POLAR WHITE)

Tekniske specifikationer

General

Wireless frequency	868 MHz
Addressing method	Electronic, Unique address embedded

Electrical

Power supply type	Batterie

Detection

Monitoring	Continuously self-checking
Alarm temperature (maximum)	+70°C
Alarm temperature (minimum)	+54°C

Physical

Colour	Bianco polare
Mounting type	Montaggio su base, Montaggio a superficie
Material (body)	Støbt ABS

Environmental

Vandal proof	No
Application temperature (maximum)	+50°C
Application temperature (typical)	+25°C
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Kompatible produkter

Kategori	Reference	Beskrivelse
Detection device	11510-ZT	ZPL1-1 ADD.LABEL 1001-1127
Detection device	11520	Zpl1-2 Add.Label 2001-2127
Detection device	11530-ZT	ZPL1-3 ADD.LABEL 3001-3127
Detection device	11540-ZT	ZPL1-4 ADD.LABEL 4001-4127



KIDDE COMMERCIAL

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57