# ZR432-2PA

## ZR432-2PA RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE



# ZR432-2PA

## ZR432-2PA RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE

## Technische Spezifikationen

### General

| | |
|---|---|
| Wireless frequency | 868 MHz |
| Addressing method | Electronic, Unique address embedded |

### Electrical

| | |
|---|---|
| Power supply type | Baterie |

### Detection

| | |
|---|---|
| Monitoring | Continuously self-checking |
| Alarm temperature (maximum) | +70°C |
| Alarm temperature (minimum) | +54°C |

### Physical

| | |
|---|---|
| Colour | Biel polarna |
| Mounting type | Montaż na podstawie, Montaż nawierzchniowy |
| Material (body) | Geformtes ABS |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Application temperature (maximum) | +50°C |
| Application temperature (typical) | +25°C |
| Environment | Drinnen |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, WEEE |
| Certification | CPR |

### Kompatible Produkte

| Kategorie | Referenz | Beschreibung |
|---|---|---|
| Detection device | 11510-ZT | ZPL1-1 ADD.LABEL 1001-1127 |
| Detection device | 11520 | Zpl1-2 Add.Label 2001-2127 |
| Detection device | 11530-ZT | ZPL1-3 ADD.LABEL 3001-3127 |
| Detection device | 11540-ZT | ZPL1-4 ADD.LABEL 4001-4127 |

KIDDE COMMERCIAL

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.