ATS1340


ATS door junction box

Product overview

The ATS1340 is designed as a universal door junction box.
The module has an incoming and outgoing data bus / power connection to achieve a proper star connection for an Advisor MASTER bus reader.
On board relays are provided to connect a door lock and a pre-warning buzzer. For high-energy locks an external 12V or 24V power supply must be connected.

Mounting location

The ATS1340 PCB can be mounted in any Advisor MASTER cabinet, which supports the size B board.
Preferably, the door junction box should be mounted close to a door which needs access control and / or alarm facilities.



Details

- Universal door interface for connecting all cables in door application
- Will reduce installation time dramatically
- Connections fully attuned at the Aritech Smart card reader
- Inputs connections for door contact and door lock contact
- Dual loop resistors already provided in the input connections
- Output connections for door lock and buzzer
- All connections short circuit protected
- Maximum up to 16x ATS1340 can be connected to the bus

ATS1340
ATS door junction box

Technical specifications

General

Accessory group	Advisor Advanced, ATS Master
Type	Modul

Electrical

Operating voltage	10.5 to 13.8 V (12 VDC nominal) 12 / 24 VDC (external power supply)
Current consumption	0 mA standby 100 mA max. (using bus 12V power supply) 500 mA (door lock max. output current at 12 / 24 VDC)

Physical

Physical dimensions	181 x 129 x 45 mm
Net weight	773 g

Environmental

Operating temperature	0 to +50°C

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:24