ZR432-2PAV

ZR432-2PAV RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE & RED VISUAL INDICATOR



ZR432-2PAV

ZR432-2PAV RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE & RED VISUAL INDICATOR

Spécifications techniques

General

Wireless frequency	868 MHz
Addressing method	Electronic, Unique address embedded

Electrical

Power supply type	Baterie

Detection

Monitoring	Continuously self-checking
Alarm temperature (maximum)	+70°C
Alarm temperature (minimum)	+54°C

Physical

Colour	Biel polarna
Mounting type	Montaż na podstawie, Montaż nawierzchniowy
Material (body)	Geformtes ABS

Environmental

Vandal proof	No
Application temperature (maximum)	+50°C
Application temperature (typical)	+25°C
Environment	Drinnen

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Produits compatibles

Catégorie	Référence	Description
Detection device	11510-ZT	ZPL1-1 ADD.LABEL 1001-1127
Detection device	11520	Zpl1-2 Add.Label 2001-2127
Detection device	11530-ZT	ZPL1-3 ADD.LABEL 3001-3127
Detection device	11540-ZT	ZPL1-4 ADD.LABEL 4001-4127

KIDDE COMMERCIAL

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57