FC-315-WA2

Fusion akustisch/optischer Funk-Signalgeber für Wandmontage, rot

General

The FC-315-WA2 is a RED, fire alarm sounder/VAD combination to be used with a wireless base. The VAD lens is specifically designed to have maximum coverage in wall mount applications. The 32 tone device is suitable for indoor use.

The sounder is quick and easy to install into the wireless base with a simple turn and lock mechanism.



The Range

The Fusion series consists of:

· Optical Smoke Detectors
· Multisensor Smoke Detectors
· A1R Heat Detectors
· CS Heat Detectors
· Sounders in red and white
· Combination Sounder VIDs and VADs
· Manual Call Points
· Interface Modules

Operating Principle

Wireless devices are often installed in buildings where wiring presents a challenge because the fabric of the building or its design is negatively affected by the use of cables. It could also be difficult to introduce cable runs into heritage buildings. It is for these architecturally sensitive buildings that the Fusion series was developed.

Every Fusion device is assigned an address from is base. This address is converted by the Fusion wireless loop interface to a device address similar to a wired device connected directly to the loop wiring.

Einzelheiten

- Dualband 868 MHz Betrieb
- 32 wählbare Töne
- Auswahl von 0,5 Hz oder 1 Hz Blitzrate
- Integrierte Audioüberwachung
- Lautstärkeregelung möglich
- Manipulationssicherer Verriegelungsmechanismus
- Drittanbieter EN zertifiziert
- Einfach zu installieren

FC-315-WA2

Fusion akustisch/optischer Funk-Signalgeber für Wandmontage, rot

Technische Spezifikationen

General

Wireless frequency	868 MHz
Compatibility	Drahtloser Sockel FC-171-002

Electrical

Power supply type	Baterias
Operating voltage	2,8 bis 5 VDC

Sounder

Output level	< 99 dB(A) @ 1 m (Tonabhängig)
Output level adjustment	Analog
Frequency	Wählbar
Selectable tones	32
No. of stages	2

VAD

Colour	Weiß
Rating	W-3.1-11.3
Floor coverage	< 132,25 m²
Flash frequency	0,5 oder 1 Hz

Physical

Physical dimensions	120 x 145 mm (Ø x H) - Inklusive Sockel
Net weight	650 g - Inklusive Sockel
Colour	Rot
Mounting type	Montagem na base
Mounting position	Parede
Mounting height	< 3.1 m
Mounting base	Sem fios

Environmental

Vandal proof	No
Operating temperature	-10°C bis 55°C
Storage temperature	5°C bis 30°C
Relative humidity	< 95 % nicht kondensierend
Environment	Drinnen
IP rating	IP54

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Certification	BOSEC, CPR
Standards	EN54-3, EN54-23

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.