ZR432-2PAV

ZR432-2PAV RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE & RED VISUAL INDICATOR



ZR432-2PAV

ZR432-2PAV RADIO DUAL OPTICAL/HEAT DETECTOR /W RADIO SOUNDER BASE & RED VISUAL INDICATOR

Tekniska specifikationer

General

Wireless frequency	868 MHz
Addressing method	Electronic, Unique address embedded

Electrical

Power supply type	Baterias

Detection

Monitoring	Continuously self-checking
Alarm temperature (maximum)	+70°C
Alarm temperature (minimum)	+54°C

Physical

Colour	Branco polar
Mounting type	Montagem na base, Montagem em superfície
Material (body)	Støbt ABS

Environmental

Vandal proof	No
Application temperature (maximum)	+50°C
Application temperature (typical)	+25°C
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Kompatibla produkter

Kategori	Referens	Beskrivning
Detection device	11510-ZT	ZPL1-1 ADD.LABEL 1001-1127
Detection device	11520	Zpl1-2 Add.Label 2001-2127
Detection device	11530-ZT	ZPL1-3 ADD.LABEL 3001-3127
Detection device	11540-ZT	ZPL1-4 ADD.LABEL 4001-4127

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57